

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number  
**WO 2005/015270 A1**

(51) International Patent Classification<sup>7</sup>: **G02B 1/10**

(21) International Application Number:  
PCT/KR2003/001676

(22) International Filing Date: 20 August 2003 (20.08.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:  
10-2003-0054991 8 August 2003 (08.08.2003) KR

(71) Applicant and

(72) Inventor: **NAM, Sang wook** [KR/KR]; 110-603 Nuri  
Apartment, Walpyung-dong, Seo-gu, Daejeon 302-791  
(KR).

(74) Agent: **YOU, Byung sun**; 610 Mannyun Officetel, 241  
Walpyung-dong, Seo-gu, Daejeon 302-282 (KR).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: LENS HAVING PROTECTION FILM THAT PREVENTS MOVING OF AXIS AND DAMAGE OF SURFACE FROM THE LENS CUTTING, AND METHOD AND COATING SOLUTION THEREOF

(57) Abstract: The present invention relates to an eyeglass, and more particularly to an eyeglass having a protective film exhibiting a greater coefficient of friction than the lens and easy peeling and removal, formed on the surface of the eyeglass lens, so as to prevent a shift of an optical axis and damage of lens surface occurring when processing the eyeglass lens, in particular a high-slip lens, and further to prevent surface damage and aging occurring during transportation or storage of lenses shipped from the a manufacturing factory and preparation thereof, and a protective film coating solution for the same.



WO 2005/015270 A1